



® 4242 Baldwin Boulevard  
 Corpus Christi, Texas  
 USA 78405-3399  
 Tel: 800-531-3111, 361-888-5591  
 Fax: 800-531-3108, 361-888-6510  
 www.hortondoors.com  
 The Automatic Choice

# ARCHITECTURAL DETAILS

## AUTOMATIC COMMERCIAL SLIDE DOORS

ProSlide® Telescoping Series 2003T

A3.27

Type: 110T Biparting O-X-SX-SX-X-O

Aug 18

### Standard Packages

Unit Width	Slide Opening	Fast Slide Panel Width	Slow Slide Panel Width	Sidelite Width	Breakout Opening	Rough Opening
9'-0" (2743)	4'- 1 1/2" (1105)	1'- 6 1/4" (464)	1'- 5 3/4" (451)	1'- 8 1/2" (521)	2'- 7 1/2" (800)	9'-0 1/2" (2756)
10'-0" (3048)	4'- 9 1/2" (1308)	1'- 8 1/4" (514)	1'- 7 3/4" (501)	1'-10 1/2" (572)	2'-11 1/2" (902)	10'-0 1/2" (3061)
12'-0" (3658)	6'- 1 1/2" (1511)	2'- 1/4" (616)	1'-11 3/4" (603)	2'- 2 1/2" (673)	3'- 7 1/2" (1105)	12'-0 1/2" (3670)
14'-0" (4267)	7'- 5 1/2" (1715)	2'- 4 1/4" (718)	2'- 3 3/4" (705)	2'- 6 1/2" (775)	4'- 3 1/2" (1308)	14'-0 1/2" (4280)
16'-0" (4877)	8'- 9 1/2" (2121)	2'- 8 1/4" (819)	2'- 7 3/4" (806)	2'-10 1/2" (876)	4'-11 1/2" (1511)	16'-0 1/2" (4890)
18'-0" (5486)	10'- 1 1/2" (3086)	3'- 0 1/4" (921)	2'-11 3/4" (832)	3'- 2 1/2" (978)	5'- 7 1/2" (1715)	18'-0 1/2" (5499)

Unit Height: 7'-6" (2286)    Rough Opening Height: 7'-6 1/4" (2292)  
 Glazing: Standard unit prep'd for 1/4" (6) glass. Glass by others.    Anodized Finish: Clear or Dark Bronze


### Options

- Custom unit widths between 9'-0" & 18'-0".
- Custom mid-rails, bottom rails and jambs.
- Transom or threshold.
- Medium or wide stile construction (slide opening will be reduced).
- Custom anodized or paint finish or stainless steel cladding

See details for options starting on p. A5.0 and Architectural Specifications on p. A7.8.

### Installation and Operation

- Door perimeter mounted within rough opening with 1/4" minimum shim space at header & jambs. Finish floor not to exceed 1/4" out of level. (See page A.3)
- Electrical: Provide 120 VAC, 60 cycle, single phase, 15 amp service (in conduit) to each unit on dedicated 20 amp circuit breaker routed to header. Maximum current draw is 3.15 amps.
- Door actuated with header mounted motion sensor at interior and exterior for detection of traffic in each direction. Door closes after time delay expires.
- Manual Locking: Exterior keylock and interior thumbturn provided at vertical strike rail. (Optional fail-safe or fail-secure autolock)



Exterior Elevations and Floor Plans

