



® 4242 Baldwin Boulevard  
 Corpus Christi, Texas  
 USA 78405-3399  
 Tel: 800-531-3111, 361-888-5591  
 Fax: 800-531-3108, 361-888-6510  
**www.hortondoors.com**  
*The Automatic Choice*

# ARCHITECTURAL DETAILS

## MANUAL SLIDE DOORS - ICU / CCU

**Profiler-ICU® Telescoping**

**A10.1.3**

**Type: 010 Biparting O-X-X-X-X-O**

Nov 16

### Standard Packages

Unit Width	Slide Opening	1st Slide Panel Width	2nd Slide Panel Width	Sidelite Width	Rough Opening Width
8'-0" (2436)	4' - 6" (1372)	1'- 4 1/2" (419)	1'- 4" (406)	1'- 6 3/4" (476)	8'-0 1/2" (2451)
9'-0" (2743)	5' - 2" (1575)	1'- 6 1/2" (470)	1'- 6" (457)	1'- 8 3/4" (527)	9'-0 1/2" (2756)
10'-0" (3150)	5'-10" (1778)	1'- 8 1/2" (521)	1'- 8" (508)	1'-10 3/4" (578)	10'-0 1/2" (3061)
11'-0" (3353)	6' - 6" (1981)	1'-10 1/2" (571)	1'-10" (559)	2'- 0 3/4" (629)	11'-0 1/2" (3353)
12'-0" (2743)	7' - 2" (2184)	2'- 0 1/2" (622)	2'- 0" (610)	2'- 2 3/4" (679)	12'-0 1/2" (3670)
14'-0" (4267)	8' - 6" (2591)	2'- 4 1/2" (724)	2'- 4" (711)	2'- 6 3/4" (781)	14'-0 1/2" (4280)

**Unit Height:** 7'-2 1/2" (2197)    **Rough Opening Height:** 7'-2 3/4" (2203)    **Anodized Finish:** Clear or Dark Bronze

**Glazing:** Standard unit prep'd for 1/4" (6) glazing.


### Options

- Positive Latching (p.A11.1)
- Custom unit widths between 8'-0" & 14'-0".
- Custom unit height to 8'-2 1/2".
- Custom mid-rails & bottom rails (p.A5.4) and jambs (p.A5.2).
- Medium stile construction (slide opening reduced by 1 1/2").
- Wide stile construction (slide opening reduced by 2 3/4").
- Custom anodized, paint or stainless steel cladding.
- Custom glazing from 5/8" to 1" (p.A11.3).



**For Architectural Specifications see pages A12.0 thru A12.3.**

### Installation and Operation

- Door perimeter mounted within curtainwall or rough opening with 1/4" minimum shim space at header & jambs. Finish floor not to exceed 1/4" out of level.
- Sliding panel rolls on nylon covered track at header for quiet, smooth, anti-friction operation.
- Standard sliding panel (X) glazed with 1/4" tempered glass (shown) can be opened with 8 to 12 lbs of force.



**Exterior Elevation and Floor Plan**



Horton Automatics reserves the right to alter its product and specifications without notice. Dimensions given in U.S. inches followed by millimeters in parenthesis.