



© 4242 Baldwin Boulevard
 Corpus Christi, Texas
 USA 78405-3399
 Tel: 800-531-3111, 361-888-5591
 Fax: 800-531-3108, 361-888-6510
 www.hortondoors.com
 The Automatic Choice

ARCHITECTURAL DETAILS

MANUAL DOORS - ICU / CCU

ICU Bi-Fold™

A10.10

Type: Pair LHR-RHR, Fold-out

May 10

Standard Packages

Unit Width	Fold Opening	Breakout Opening	Fold Reach	Breakout Reach	Rough Opening Width
6'-0" (1829)	4'-4" (1343)	4'-11" (1505)	1'-0" (305)	2'-4 1/2" (730)	6'-0 1/2" (1841)
6'-5 1/2" (1968)	4'-10" (1482)	5'-4" (1645)	1'-2" (356)	2'-7 1/4" (794)	6'-6" (1981)
7'-0" (2134)	5'-4" (1648)	5'-11" (1810)	1'-3" (381)	2'-10 1/2" (876)	7'-0 1/2" (2146)
8'-0" (2428)	6'-4" (1953)	6'-11" (2115)	1'-6" (457)	3'-4 1/2" (1029)	8'-0 1/2" (2451)

Unit Height: 7'-2 3/4" (2203), **Rough Opening Height:** 7'-3" (2210)
Glazing: Standard unit prep'd for 1/4" (6) glass. Glass provided by others.

Anodized Finish:
 Clear or Dark Bronze

Options

- Fold-In Panels (Fold-Out Panels Shown)
- Additional Muntins and/or Push Bars
- Custom Glazing, Finishes and Sizes
- Transom

For standard and optional equipment details see Arch. Specs., page A14.0, and Spec. Details on pages A11.0 & A11.1.

Installation and Operation

- Door perimeter mounted within curtainwall or rough opening with 1/4" minimum shim space at header & jambs. Finish floor not to exceed 1/4" out of level. (See page A9.1)
- Standard folding panel glazed with 1/4" tempered glass (shown) can be opened with 4 to 6 lbs of force.

