

### Standard Packages

Unit Width	Slide Opening	Breakout Opening	Slide Panel Width	Sidelite Width	Rough Opening Width
8'-0" (2438)	3'-0" (914)	6'-9 1/2" (2070)	2'-0" (610)	2'-0 1/2" (622)	8'-0 1/2" (2146)
9'-0" (2743)	3'-6" (1067)	7'-9 1/2" (2375)	2'-3" (686)	2'-3 1/2" (699)	9'-0 1/2" (2756)
10'-0" (3048)	4'-0" (1219)	8'-9 1/2" (2680)	2'-6" (762)	2'-6 3/4" (781)	10'-0 1/2" (3061)
12'-0" (3658)	5'-0" (1524)	10'-9 1/2" (3289)	3'-0" (914)	3'-0 3/4" (933)	12'-0 1/2" (3670)
14'-0" (4267)	6'-0" (1829)	12'-9 1/2" (3899)	3'-6" (1067)	3'-6 3/4" (1086)	14'-0 1/2" (4280)
16'-0" (4877)	7'-0" (2134)	14'-9 1/2" (4509)	4'-0" (1219)	4'-0 3/4" (1238)	16'-0 1/2" (4890)

  

<b>Unit Height:</b> 7'-2 1/2" (2197) <b>Rough Opening Height:</b> 7'-2 3/4" (2203) <b>Glazing:</b> Standard unit prep'd for 1/4" (6) glazing.	<b>Anodized Finish:</b> Clear or Dark Bronze
-----------------------------------------------------------------------------------------------------------------------------------------------------	----------------------------------------------------

### Options

- Positive Latching (p.A11.1) (slide opening reduced by 4 1/2").
- Full Size (4" x 6") Profiler® Header (p.A11.0)
- Custom unit widths between 8'-0" & 16'-0".
- Custom unit height to 8'-2 1/2".
- Custom mid-rails & bottom rails (p. A5.4) and jambs (p.A5.2).
- Medium stile construction (slide opening reduced by 3").
- Wide stile construction (slide opening reduced by 5 1/2").
- Custom anodized, paint or stainless steel cladding.
- Custom glazing from 5/8" to 1" (p.A5.5).

For Architectural Specifications see pages A12.0 thru A12.3.

### Installation and Operation

- Door perimeter mounted within curtainwall or rough opening with 1/4" minimum shim space at header & jambs. Finish floor not to exceed 1/4" out of level. (See page A9.1)
- Sliding panels roll on nylon covered track at header for quiet, smooth, anti-friction operation.
- Standard sliding panel (SX) glazed with 1/4" tempered glass (shown) can be opened with 8 to 12 lbs of force. Panels can swing out min. 90° at full open position requiring no more than 50 lbs of force applied at the strike stile after 'SO' flush bolt released.
- Finger Safety: When sliding open, strike rail of sliding panel will stop 3 1/2" (89) short of adjacent sidelite. Result is slide opening.

