



© 4242 Baldwin Boulevard  
 Corpus Christi, Texas  
 USA 78405-3399  
 Tel: 800-531-3111, 361-888-5591  
 Fax: 800-531-3108, 361-888-6510  
 www.hortondoors.com  
 The Automatic Choice

# ARCHITECTURAL DETAILS

MANUAL SLIDE DOORS - ICU / CCU

**Profiler-ICU® Smoke Rated Trackless**  
**Type: 310T Telescoping SO-SX-SX or SX-SX-SO**

**A10.20**  
 Jan 09

## Standard Packages

Unit Width	Slide Opening	Breakout Opening	1st Slide Panel Width	2nd Slide Panel Width	Sidelite Width	Rough Opening Width
7'-0" (2134)	3'-4 1/4" (1022)	6'-1" (1854)	2'-10 3/4" (883)	2'-4 1/4" (718)	1'-10 1/4" (565)	7'-0 1/2" (2146)
8'-0" (2438)	4'-0 1/4" (1225)	7'-1" (2159)	3'-2 3/4" (984)	2'-8 1/4" (826)	2'-2 1/4" (668)	8'-0 1/2" (2451)
9'-0" (2743)	4'-8 1/4" (1429)	8'-1" (2464)	3'-6 3/4" (1086)	3'-0 1/4" (921)	2'-6 1/4" (768)	9'-0 1/2" (2756)
10'-0" (3048)	5'-4 1/4" (1632)	9'-1" (2769)	3'-10 3/4" (1187)	3'-4 1/4" (1022)	2'-10 1/4" (870)	10'-0 1/2" (3061)
11'-0" (3048)	6'-0 1/4" (1835)	10'-1" (3073)	4'-2 3/4" (1289)	3'-8 1/4" (1024)	3'-2 1/4" (971)	11'-0 1/2" (3112)
12'-0" (3048)	6'-8 1/4" (2038)	11'-1" (3099)	4'-6 3/4" (1391)	4'-0 1/4" (1226)	3'-6 1/4" (1073)	12'-0 1/2" (3670)

**Unit Height:** 7'-2 1/2" (2197), **Rough Opening Height:** 7'-2 3/4" (2203)  
**Glazing:** Standard unit prep'd for 1/4" (6) glazing.

**Anodized Finish:** Clear or Dark Bronze

## Compliant with UL 1784 - Air Leakage Test of Door Assemblies

- Gasketing is high temperature silicone.
- All panels wet glazed with red high temperature silicone sealant at corners.
- All seals are factory installed to maintain UL 1784 rating.

See Arch. Specifications, page A13.0 and Specification Details page A11.1.

## Installation and Operation

- Door perimeter mounted within curtainwall or rough opening with 1/4" minimum shim space at header & jambs. Finish floor not to exceed 1/4" out of level. (See page A9.1)
- Sliding panels roll on nylon covered track at header for quiet, smooth, anti-friction operation.
- Standard sliding panel (SX) glazed with 1/4" tempered glass (shown) can be opened, after positive latch is released, with 4 to 6 lbs of force. At full open position panels can swing out 90°, after SO flush bolt is released, requiring no more than 50 lbs of force applied at the strike stile.

