

Standard Packages

Unit Width	Slide Opening	Breakout Opening	Slide Panel Width	Sidelite Width	Rough Opening Width
7'-0" (2134)	2'-8 7/8" (835)	6'-3" (1905)	3'-8 3/8" (1127)	3'-2 3/8" (975)	7'-0 1/2" (2146)
8'-0" (2438)	3'-2 7/8" (987)	7'-3" (2210)	4'-2 3/8" (1280)	3'-8 3/8" (1127)	8'-0 1/2" (2451)
8'-6" (2591)	3'-5 7/8" (1063)	7'-9" (2362)	4'-5 3/8" (1356)	3'-11 3/8" (1203)	8'-6 1/2" (2604)
9'-0" (2743)	3'-8 7/8" (1140)	8'-3" (2515)	4'-8 3/8" (1432)	4'-2 3/8" (1280)	9'-0 1/2" (2756)

Unit Height: 7'-2 1/2" (2197) Rough Opening Height: 7'-2 3/4" (2203) Glazing: Standard unit prep'd for 1/4" (6) glazing.	Anodized Finish: Clear or Dark Bronze
---	--

Compliant with UL 1784 - Air Leakage Test of Door Assemblies

- Gasketing material is high temperature silicone.
- All panels wet glazed with red high temperature silicone sealant at corners.
- All seals are factory installed to maintain UL 1784 rating.

Options

- Electro-Magnet Hold-Open

See Arch. Specifications starting on page A21.0 .

Installation and Operation

- Door perimeter mounted within curtainwall or rough opening with 1/4" minimum shim space at header & jambs. Finish floor not to exceed 1/4" out of level. (See page A9.1)
- Sliding panel rolls on nylon covered track in header for quiet, smooth, anti-friction operation.
- Standard sliding panel (SX) can be opened, after positive latch is released, with 8 to 12 lbs of force. Unless "Hold-Open" is engaged, sliding panel will immediately begin to close with 6-8 lbs of force. Optional electro-magnet hold-open ties to fire alarm system and will automatically close the door when alarm is activated. Panels can swing out 90° at full open position, after flush bolt is released, requiring no more than 50 lbs of force applied at the strike stile.
- Strike rail of sliding panel will stop 9" (229) short of adjacent sidelite. Result is slide opening.

