



® 4242 Baldwin Boulevard
 Corpus Christi, Texas
 USA 78405-3399
 Tel: 800-531-3111, 361-888-5591
 Fax: 800-531-3108, 361-888-6510
 www.hortondoors.com
 The Automatic Choice

ARCHITECTURAL DETAILS

POWER SWING DOOR OPERATORS

EasyAccess® Series 7100 Surface Applied Double Egress with Parallel Inswing Arm and Track

B2.4.2
 Aug 18

Standard Packages

Double Egress Units	
Types: LH-RHR, LHR-RH	
Door Pair Width	Header Width
5'-0" (1524)	5'-3" (1600)
6'-0" (1829)	6'-3" (1905)
7'-0" (2133)	7'-3" (2210)
Anodized Finish: Clear or Dark Bronze	

Installation and Operation

- Swing door header is surface mounted onto frame and connecting arm assembly is mounted to face of door panel. Frame and door panel to be provided by others (see "Typical Mounting and Rough-In Wiring" p.B1.2.)
- Electrical: Provide 120 VAC , 60 cycle, single phase, 15 amp service (in conduit) to each swing door unit on a dedicated 20 amp circuit breaker routed into header. Maximum current draw is 3.15 amps
- 2-Way Traffic: Unit to be actuated by push button or push plate on each side of unit (see "Push Button and Push Plate Switches" p.E2.4).

For additional equipment information see Architectural Specifications B6.1.

