



® 4242 Baldwin Boulevard
 Corpus Christi, Texas
 USA 78405-3399
 Tel: 800-531-3111, 361-888-5591
 Fax: 800-531-3108, 361-888-6510
 www.hortondoors.com
 The Automatic Choice

SPECIFICATION DETAILS

SECURITY REVOLVING DOOR ENTRANCES

Optional Exit Lane Breach Control

Early Warning Detection for Security Series 9130AP & 9131AP

F3.14
 May 19

Standard Packages

Corridor Width	Package Type
3'-4" (1016) to 4'-0" (1219)	C16300 Single Sensor Package
4'-1" (1143) to 6'-8" (2032)	C16300-1 Double Sensor Package
6'-9" (2057) to 10'-0" (3048)	C16300-2 Triple Sensor Package

The Early Warning Detection and Lockdown option/feature provides another layer of security for early detection of a possible breach attempt.

Options

- One or 2 Sidelites (to create required corridor).
- Special dimensions available (contact factory).

Operation

If a pedestrian approaches the door from the Unauthorized Entry side, while there is no traffic exiting the door, the Early Warning Detection (Motion Detection 1) signals an alarm and/or initiates a red flashing light to warn that pedestrian they are entering a prohibited "Do Not Enter" area. Traffic flow exiting the door in the intended direction (Motion Detection 2) continues uninterrupted. However, if that pedestrian continues undeterred toward the door in a breach attempt, the Lockdown Detection signals the revolving door to instantly stop and lockdown.

